

# AXIS P3245-V Network Camera

## Streamlined HDTV 1080p fixed dome

AXIS P3245-V offers excellent image quality in HDTV 1080p under any light conditions. This streamlined, IK10-rated camera features Forensic WDR to provide clarity when there's both dark and light areas in the scene. And, Lightfinder 2.0 delivers video with more life-like colors and sharp video of moving objects. Including a varifocal lens with remote zoom and focus capabilities, it eliminates the need for hands-on fine tuning. This camera features enhanced security features to ensure the integrity and authenticity of the camera's firmware. Furthermore, it offers Axis Zipstream with support for H.264/H.265, which significantly reduces bandwidth and storage requirements.

- > [HDTV 1080p video quality](#)
- > [Remote zoom and focus](#)
- > [Lightfinder 2.0 and Forensic WDR](#)
- > [Zipstream supporting H.264 and H.265](#)
- > [Signed firmware and secure boot](#)



# AXIS P3245-V Network Camera

<b>Camera</b>		MQTT subscribe
<b>Image sensor</b>	1/2.8" progressive scan RGB CMOS	<b>Event actions</b>
<b>Lens</b>	Varifocal, 3.4–8.9 mm, F1.8 Horizontal field of view: 100°–36° Vertical field of view: 53°–20° Remote zoom and focus, P-Iris control, IR corrected	Record video: SD card and network share Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email Pre- and post-alarm video or image buffering for recording or upload Notification: email, HTTP, HTTPS, TCP, and SNMP trap MQTT publish Overlay text, make call
<b>Day and night</b>	Automatically removable infrared-cut filter	<b>Data streaming</b>
<b>Minimum illumination</b>	<b>With Forensic WDR and Lightfinder 2.0:</b> Color: 0.1 lux at 50 IRE, F1.8 B/W: 0.02 lux at 50 IRE, F1.8	Event data
<b>Shutter speed</b>	1/66500 s to 2 s	<b>Built-in installation aids</b>
<b>Camera angle adjustment</b>	Pan ±180°, tilt ±75°, rotation ±175°	Pixel counter, remote focus, remote zoom
<b>System on chip (SoC)</b>		<b>Analytics</b>
<b>Model</b>	ARTPEC-7	<b>AXIS Object Analytics</b>
<b>Memory</b>	1024 MB RAM, 512 MB Flash	Object classes: humans, vehicles Trigger conditions: line crossing, object in area Up to 10 scenarios Metadata visualized with color-coded bounding boxes Polygon include/exclude areas Perspective configuration ONVIF Motion Alarm event
<b>Compute capabilities</b>	Machine learning processing unit (MLPU)	<b>Applications</b>
<b>Video</b>		<b>Included</b> AXIS Object Analytics AXIS Motion Guard, AXIS Fence Guard, AXIS Loitering Guard AXIS Video Motion Detection, active tampering alarm <b>Supported</b> AXIS Occupancy Estimator, AXIS People Counter, AXIS Tailgating Detector, AXIS Direction Detector, AXIS Random Selector AXIS Live Privacy Shield Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://axis.com/acap">axis.com/acap</a>
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC) Baseline, Main and High Profiles H.265 (MPEG-H Part 2/HEVC) Main Profile Motion JPEG	<b>General</b>
<b>Resolution</b>	1920x1080 to 160x90	<b>Casing</b>
<b>Frame rate</b>	<b>With WDR:</b> 25/30 fps with power line frequency 50/60 Hz <b>Without WDR:</b> 50/60 fps with power line frequency 50/60 Hz	IP52-rated, IK10 impact-resistant polycarbonate casing with hard-coated dome and dehumidifying membrane Encapsulated electronics and captive screws Color: white NCS S 1002-B For repainting instructions and impact on warranty, contact your Axis partner.
<b>Video streaming</b>	Multiple, individually configurable streams in H.264, H.265, and Motion JPEG Axis Zipstream technology for H.264 and H.265 Controllable frame rate and bandwidth VBR/ABR/MBR H.264/H.265	<b>Mounting</b>
<b>Multi-view streaming</b>	Up to 2 individually cropped out view areas in full frame rate	Mounting bracket with holes for junction box (double-gang, single-gang, and 4" octagon) and for wall or ceiling mount ¼"-20 UNC tripod screw thread
<b>Image settings</b>	Compression, color saturation, brightness, sharpness, contrast, local contrast, white balance, day/night threshold, tone mapping, exposure control (including automatic gain control), exposure zones, defogging, Forensic WDR: up to 120 dB depending on scene, barrel distortion correction, fine tuning of low-light behavior, dynamic text and image overlay, privacy masks, mirroring, rotation: 0°, 90°, 180°, 270°, including Corridor Format	<b>Sustainability</b>
<b>Pan/Tilt/Zoom</b>	Digital PTZ, preset positions	PVC free BVR/CFR free
<b>Audio</b>		<b>Power</b>
<b>Audio input/output</b>	Two-way audio connectivity via optional AXIS T61 Audio and I/O Interfaces with portcast technology	Power over Ethernet (PoE) IEEE 802.3af/802.3at Type 1 Class 2 Typical 3.5 W, max 5.7 W
<b>Network</b>		<b>Connectors</b>
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X (EAP-TLS) <sup>a</sup> network access control, digest authentication, user access log, centralized certificate management, brute force delay protection, signed firmware, secure boot	RJ45 10BASE-T/100BASE-TX PoE Audio and I/O connectivity via AXIS T61 Audio and I/O Interfaces with portcast technology
<b>Supported protocols</b>	IPv4, IPv6 USGv6, ICMPv4/ICMPv6, HTTP, HTTP/2, HTTPS <sup>a</sup> , TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, SFTP, CIFS/SMB, SMTP, mDNS (Bonjour), UPnP <sup>®</sup> , SNMP v1/v2c/v3 (MIB-II), DNS/DNSv6, DDNS, NTP, RTSP, RTP, SRTP, TCP, UDP, IGMPv1/v2/v3, RTCP, ICMP, DHCPv4/v6, ARP, SOCKS, SSH, SIP, LLDP, CDP, MQTT v3.1.1, Syslog, Link-Local address (ZeroConf)	<b>Storage</b>
<b>System integration</b>		Support for microSD/microSDHC/microSDXC card Support for SD card encryption (AES-XTS-Plain64 256bit) Recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://axis.com">axis.com</a>
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://axis.com">axis.com</a> One-click cloud connection ONVIF <sup>®</sup> Profile G, ONVIF <sup>®</sup> Profile M, ONVIF <sup>®</sup> Profile S, and ONVIF <sup>®</sup> Profile T, specification at <a href="http://onvif.org">onvif.org</a> Support for Session Initiation Protocol (SIP) for integration with Voice over IP (VoIP) systems, peer to peer or integrated with SIP/PBX	<b>Operating conditions</b>
<b>Event conditions</b>	Analytics, edge storage events, virtual inputs through API	0 °C to 50 °C (32 °F to 122 °F) Humidity 10–85% RH (non-condensing)
		<b>Storage conditions</b>
		-40 °C to 65 °C (-40 °F to 149 °F) Humidity 5–95% RH (non-condensing)
		<b>Approvals</b>
		EMC EN 55032 Class A, EN 50121-4, IEC 62236-4, EN 55024, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-3(A)/NMB-3(A), VCCI Class A, RCM AS/NZS CISPR 32 Class A, KC KN32 Class A, KC KN35 <b>Safety</b> IEC/EN/UL 62368-1, IS 13252 <b>Environment</b> IEC 60068-2-1, IEC 60068-2-14, IEC 60068-2-2, IEC 60068-2-27, IEC 60068-2-6, IEC 60068-2-78 IEC/EN 60529 IP52, IEC/EN 62262 IK10 <b>Network</b> NIST SP500-267
		<b>Dimensions</b>
		Height: 103 mm (4.06 in)

	ø 149 mm (5.87 in)
<b>Weight</b>	650 g (1.4 lb)
<b>Included accessories</b>	Installation guide, Windows® decoder 1-user license, drill template, Resistorx® T20 L-key, cable gaskets, connector guard
<b>Optional accessories</b>	AXIS TP3201 Recessed Mount, AXIS T94K01D Pendant Kit, AXIS T6101 Audio and I/O Interface, AXIS T6112 Audio and I/O Interface, AXIS ACI Conduit Adapters, Axis mounts, smoked dome, black casing For more accessories, see <a href="http://axis.com">axis.com</a>
<b>Video management software</b>	AXIS Companion, AXIS Camera Station, video management software from Axis Application Development Partners available at <a href="http://axis.com/vms">axis.com/vms</a>

**Languages** English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese

**Warranty** 5-year warranty, see [axis.com/warranty](http://axis.com/warranty)

- a. *This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (openssl.org), and cryptographic software written by Eric Young (eay@cryptsoft.com).*

Environmental responsibility:

[axis.com/environmental-responsibility](http://axis.com/environmental-responsibility)